- (C) The operator complies with the following requirements:
- (1) The restraint system must be properly secured to an approved forward-facing seat or berth;
- (2) The child must be properly secured in the restraint system and must not exceed the specified weight limit for the restraint system; and
- (3) The restraint system must bear the appropriate label(s).
- (b) Unless otherwise stated, this section does not apply to operations conducted under part 121, 125, or 135 of this chapter. Paragraph (a)(3) of this section does not apply to persons subject to §91.105.

[Doc. No. 26142, 57 FR 42671, Sept. 15, 1992, as amended by Amdt. 91-250, 61 FR 28421, June 4 1996]

## §91.109 Flight instruction; Simulated instrument flight and certain flight tests.

- (a) No person may operate a civil aircraft (except a manned free balloon) that is being used for flight instruction unless that aircraft has fully functioning dual controls. However, instrument flight instruction may be given in a single-engine airplane equipped with a single, functioning throwover control wheel in place of fixed, dual controls of the elevator and ailerons when—
- (1) The instructor has determined that the flight can be conducted safely; and
- (2) The person manipulating the controls has at least a private pilot certificate with appropriate category and class ratings.
- (b) No person may operate a civil aircraft in simulated instrument flight unless—
- (1) The other control seat is occupied by a safety pilot who possesses at least a private pilot certificate with category and class ratings appropriate to the aircraft being flown.
- (2) The safety pilot has adequate vision forward and to each side of the aircraft, or a competent observer in the aircraft adequately supplements the vision of the safety pilot; and
- (3) Except in the case of lighter-thanair aircraft, that aircraft is equipped with fully functioning dual controls. However, simulated instrument flight

- may be conducted in a single-engine airplane, equipped with a single, functioning, throwover control wheel, in place of fixed, dual controls of the elevator and ailerons, when—
- (i) The safety pilot has determined that the flight can be conducted safely; and
- (ii) The person manipulating the controls has at least a private pilot certificate with appropriate category and class ratings.
- (c) No person may operate a civil aircraft that is being used for a flight test for an airline transport pilot certificate or a class or type rating on that certificate, or for a part 121 proficiency flight test, unless the pilot seated at the controls, other than the pilot being checked, is fully qualified to act as pilot in command of the aircraft.

## §91.111 Operating near other aircraft.

- (a) No person may operate an aircraft so close to another aircraft as to create a collision hazard.
- (b) No person may operate an aircraft in formation flight except by arrangement with the pilot in command of each aircraft in the formation.
- (c) No person may operate an aircraft, carrying passengers for hire, in formation flight.

## §91.113 Right-of-way rules: Except water operations.

- (a) *Inapplicability*. This section does not apply to the operation of an aircraft on water.
- (b) General. When weather conditions permit, regardless of whether an operation is conducted under instrument flight rules or visual flight rules, vigilance shall be maintained by each person operating an aircraft so as to see and avoid other aircraft. When a rule of this section gives another aircraft the right-of-way, the pilot shall give way to that aircraft and may not pass over, under, or ahead of it unless well clear.
- (c) *In distress*. An aircraft in distress has the right-of-way over all other air traffic.
- (d) *Converging.* When aircraft of the same category are converging at approximately the same altitude (except head-on, or nearly so), the aircraft to the other's right has the right-of-way.